



# M-310 Retrofit Monitoring

**MATOS® Monitoring can now be retrofitted to any fridge, freezer, cool-room or airspace. This can be achieved with the use of our new MATOS® M-310 stand-alone monitoring unit. Developed and built in New Zealand, the M-310 is a robust, secure monitoring unit that is wifi and cellular compatible for all your monitoring environments.**



MATOS® M-310 is a standalone monitoring unit that is quick and easy to install and provides most of the premium MATOS® Monitoring features in a compact, robust enclosure:

- Fully automatic, online monitoring – [www.matosmonitoring.com](http://www.matosmonitoring.com)
- Requires internet connection (wifi & cellular options available)
- Wall mount or benchtop monitoring unit
- Supports up to 6 digital temperature sensors/probes
- Supports 2 digital inputs (I/O) e.g. monitor power or door status
- Variable probe lengths and configurations available
- 24 hour Battery Backup with instant power switching
- 30 days internal log memory
- Cloud storage data integrity guaranteed for at least 10 years
- New Zealand and Australian compliant.

*Standard MATOS® Monitoring terms and conditions apply.  
Extra charges may be applicable for excess sms alerts.*

*We also offer tailor-made options for retrofitting our complete Fridge Rescue System and Monitoring M-R01 and M-R02 units into compatible fridges and freezers.*

**ROLLEX MEDICAL (AUST) PTY LTD**

11 Vangeli Street, Arndell Park, NSW 2148

Phone: 1300 880 441 | Fax: 1300 880 451 | Email: [sales@rollexmedical.com](mailto:sales@rollexmedical.com) | [www.rollexmedical.com.au](http://www.rollexmedical.com.au)

**Matos® Monitoring is a web-based, automatic, temperature monitoring system, enabling direct access to your fridge temperatures and records anywhere, at any time.**



### Fully Automatic Monitoring

No manual data logging or computer programme required.

### Dedicated Server

Matos® Monitoring features a dedicated, off site, secure server ensuring fast access speeds when information is critical.

### SMS Alerting

Temperature excursions and status alarms are sent via text message within seconds.

### Ease of Access

Access fridge temperatures and statuses from any web-capable device such as a computer, smartphone or tablet.

### Clear Concise Information

See temperature history and fridge status at a glance with easy to read colour coded indicators.

### Full Alert History

Complete alert history makes audit trails a breeze. See who has responded and action taken with the click of a button.

### Wireless Capability

Internet connection via wired or secure wireless network.

### Automatic and Custom Reports

Get reports delivered direct to your email inbox or create custom PDF reports for any period.

### Robust Database

Double backup and RAID system ensures data is kept safe and secure for over 10 years.

### Battery Backup

With Matos® smart compact UPS built into the fridge the temperature monitoring will continue during a power failure, ensuring an uninterrupted temperature log. (Backup time up to 13 hours).

Automatic battery maintenance and smart-charging cycle ensures maximum battery life.

### Outgoing Communication Only

As there are no incoming connections to the monitoring device the network security of your business is never compromised.

### Self Reporting/Analysing

Self monitored device ensures any hardware problems are reported to the user ensuring quick response.

Take a look at the Matos® demonstration site.

[www.matosmonitoring.com](http://www.matosmonitoring.com) using the following login:

Username: **matosdemo1** / Password: **matosdemo1**